



## Universal connection and branching sleeves



### Product features

These universal connection and branching sleeves were especially developed to provide simple and absolutely reliable protection for telecommunication and electrical applications. They can be installed outdoors, in pits and below ground, can be opened and reused as required and are provided with protection category IP68. The sleeves basically consist of only 3 parts: sleeve body, rubber end cap and cover. Cable ties, lubricant and a cutter are enclosed and guarantee problem-free processing of the sleeve without additional tools.

### Assortment

Item no.	Description
206290	Connection sleeve Ø 170 mm×72 mm with 4 inlets Ø 5-14 mm
197983	Connection sleeve Ø 280 mm×100 mm with 4 inlets Ø 7-25 mm
216551	Connection sleeve Ø 330 mm×170 mm with 6×Ø 8-26 mm/1×Ø 10-33 mm/1×Ø 10-42 mm

### Technical Data

Use:	Soil or outdoor area
Dimensions:	
– Item no. 206290:	170×72 mm
– Item no. 197983:	280×100 mm
– Item no. 197983:	330×170 mm
Material:	Polypropylene black
Screw connection:	Cover made of polypropylene
Cable receptacle:	
– Item no. 206290:	4×5-14 mm
– Item no. 197983:	4×7-25 mm
– Item no. 197983:	6×Ø 8-26 mm/ 1×Ø 10-33 mm/ 1×Ø 10-42 mm
Strain relief:	Mechanically via the cable grommet after insertion
Tensile stress:	min. 80 N/mm
Temperature range:	-30°C to +65°C
Test:	IP68, IM22
Electronics:	1 kV, ÖVE
Test number:	VAEE 36221

### Scope of delivery Item no. 197983

