

TorchLED torch light "Railway"
battery or accu operated



Technical data lamp

| | |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply: | 4 pcs AA 1.5V batteries or 4 pcs AA 1.5V accu cells |
| Luminous flux: | 185lm (2 LED white full light) |
| Protection category: | IP54 |
| Light source: | LED |
| Equipment: | 2×white/4×red |
| Housing: | – PA6-housing, with rubber overmolded handle lots (non-slip) – freestanding – Belt clip (chrome steel) – mechanical resistant |
| Temperature range: | –20°C to +45°C |
| Dimension (L×W×H): | 68×115.5×35mm |
| Weight: | approx. 115g without cells |

Technical data charging station

| | |
|--------------------|--------------------------------------------------------------------------------|
| Operating voltage | 100-240VAC / 12-48VDC |
| Power supply: | 700mA charging current |
| Protection class: | IP44 |
| Housing: | – ABS – Wall or table mounting possible – Lamp retaining clip |
| Contacts: | spring steel, gold plated |
| Charging time: | at 1'900mAh cells max. 4h |
| Temperature range: | 0°C to +40°C |
| Dimension (L×W×H): | – Charging station: 86.6×79.6×44mm – 5-fold charging station: 500×220×125mm |

Features

Unique operating of switching element by colored marking allows a safe work in a marshalling-yard, also easy to handle with gloves



Simple opening of casing to change batteries, safe closing by spring lock. Unique insertion of batteries (reverse battery protection).

Spare parts:

Spare parts are available because of the in-house production.

Our assortment

171262* TorchLED torch light "Railway", yellow, incl. hand strap

Accessories/spare parts

| | |
|--------|--------------------------------------------------------------------------------------------------------------------------|
| 860276 | TorchLED charging station, 100-240VAC, incl. 1.5m cable with plug-in transformer |
| 133537 | TorchLED charging station, 12-48VDC, incl. 1.5m cable with cigarette plug |
| 860471 | TorchLED charging station, 12-48VDC, incl. 1.5m cable without plugs and sockets |
| 130407 | TorchLED wall charging station 5-fold, 100-240VAC/700mA, max. 15VDC, incl. 3m main supply 3×1.0mm ² black T12 |
| 860274 | Accu-NiMH 1.2V/1900mAh HR6-AA |
| 860275 | Alkaline battery 1.5V/LR6-AA |
| 168655 | Magnetic foil 60×20×2mm |
| 128785 | Wall bracket – empty |
| 860335 | TorchLED belt pouch 72×127×35mm |

*For a TorchLED Railway, art. 860274 or 860275 is 4×needed.