

TorchLED torch light «Railway» - Safety guard

battery or accu operated







Technical data lamp

Power supply: 4 pcs AA 1.5V batteries (3'000 mA) or 4 pcs AA 1.5V accu cells (1'900 mA) 90 lm (1 LED white full light) Luminous flux:

Protection category: IP54 Light source: LED

Equipment: 1×white/7×red

- PA6-housing, with rubber overmolded Housing:

handle lots (non-slip)

- freestanding - belt clip (chrome steel) - mechanical resistant - signal coleur yellow

- integrated attachment points for hand

strap and belt -20°C to +45°C Temperature range: Dimension: 68×115.5×35 mm Weight: ~115g without cells

Technical data charging station

Operating voltage 100-240 VAC/12-48 VDC 700 mA charging current Power supply: - ARS Housing:

- wall or table mounting possible

- lamp retaining clip

- cut-outs on the underside of the housing prevent cable kinking and breakage

Contacts: spring steel, gold plated Charging time: at 1'900 mAh cells max. 5h

Temperature range: Dimension:

– Charging station:

 0° C to $+40^{\circ}$ C

86.6×79.6×44 mm -5-fold charging station: 500×220×125 mm

Features

Red light appears each time a button is pressed. This enables trains to be stopped quickly in an emergency in accordance with the SBB manual. The luminaire also includes integrated white light. It can also be used as a torch. The unmistakable operation of the switching element through colour coding enables work to be carried out safely in marshalling yards. It is easy to handle even when wearing winter gloves.

Function



- tap: Switching the light on and off

- when switched on, all red LEDs light up operation with white light, Switch to red light

- further operation switches light off



On/ Function selection

On/Off

- tap: Switching red light on - further operation switches to white light

each further operation switches between

white and red light

Assortment

125385 ✓ TorchLED torch light, work and inspection light, 1×LED white / 7×LED red

Accessories/spare parts

860276 ✓ TorchLED charging station, 100-240 VAC, incl. 1.5 m cable with plug-in transformer

861085 TorchLED charging station, 12-48 VDC, incl. 1.5 m cable with cigarette plug

860440 ✓ TorchLED charging station, 12-48 VDC, incl. 1.5 m cable without plugs and sockets

130407 ✓ TorchLED wall charging station 5-fold, 100-240 VAC/700 mA, max. 15 VDC, incl. 3 m main supply 3×1.0 mm² black T12

860274 ✓ Accu-NiMH 1.2V/1900 mAh HR6-AA

860275 ✓ Alkaline battery 1.5 V/LR6-AA

168655 ✓ Magnetic foil 60×20×2mm

128785 ✓ Wall bracket – empty

860335 ✓ TorchLED belt pouch 72×127×35 mm

For a TorchLED Railway, art. 860274 or 860275 is 4×needed.



