

Conductor connector



Item no.	172623 ✓
Designation	TeeTube «Y-distributor 3p» for cable Ø 7 - 13.5 mm
No. of poles	3
Clamp	screw
Cable diameter	max. 1.5 mm ²
Cable diameter min - max	7 mm - 13.5 mm
Protection category	IP68 2bar (20m/1H)
Rated current and voltage	32A 250V
Temperature range	-40°C to +125°C



Item no.	172622 ✓
Designation	TeeTube «T-distributor 3p» for cable Ø 7 - 10.5 mm
No. of poles	3
Clamp	screw
Cable diameter	max. 4 mm ²
Cable diameter min - max	7 mm - 10.5 mm
Protection category	IP68 2bar (20m/1H)
Rated current and voltage	32A 450V
Temperature range	-40°C to +125°C



Item no.	168467 ✓
Designation	TeeTube «mini 3p» for cable Ø 7 - 12 mm
No. of poles	3
Clamp	screw
Cable diameter	max. 4 mm ²
Cable diameter min - max	7 mm - 12 mm
Protection category	IP68 1bar (10m/1H)
Rated current and voltage	32A 450V
Temperature range	-40°C to +125°C



Item no.	180547 ✓
Designation	TeeTube, 5p for cable Ø 7 - 13.5 mm
No. of poles	5
Clamp	screw
Cable diameter	max. 4 mm ²
Cable diameter min - max	7 mm - 13.5 mm
Protection category	IP68 5bar (50m/1H)
Rated current and voltage	32A 450V
Temperature range	-40°C to +125°C



Item no.	198699 ✓
Designation	Phoenix «connector 3p», quick connector for cable Ø 5-9.5 mm
No. of poles	3
Clamp	Quickon-fast connection
Cable diameter	0.5 mm ² - 1.5 mm ²
Cable diameter min - max	5 mm - 9.5 mm
Protection category	IP68/69K (2m/24H)
Rated current and voltage	17.5A 690V
Temperature range	-40°C to +100°C

